

## Air Motor Driven Models

gpm	psi	Model	pump rpm	hyd hp	psi (air required)	cfm (air required)
<b>2.0 hp, 3000 RPM</b>						
1.7	725	0702A2H	3000	0.94	100	30
2.5	450	0503A2H	3000	0.94	100	30
<b>4.0 hp, 3000 RPM</b>						
1.6	1175	1102A2H	3000	1.5	90	65
2.5	975	1003A2H	3000	1.7	100	70
<b>6.0 hp, 3000 RPM, operated at 2.6 hp, 1725 RPM</b>						
2.1	875	0902A4H	1725	1.6	60	55
2.1	1450	1502A4H	1725	2.2	80	70
3.0	725	0703A4H	1725	1.6	60	55
3.0	1200	1203A4H	1725	2.6	100	85
4.3	825	0904A4H	1725	2.6	100	85
<b>8.0 hp, 2500 RPM, operated at 4.2 hp, 1725 RPM</b>						
2.1	1950	2002A4H	1725	2.95	70	103
3.1	1875	1903A4H	1725	4.2	100	130
4.2	1450	1504A4H	1725	4.2	100	130
4.8	1250	1305A4H	1725	4.2	100	130
<b>16 hp, 2000 RPM operated at 8.5 hp, 1725 RPM</b>						
3.1	2325	2403A4H	1725	5.25	60	160
3.8	2850	2804A4H	1725	8.5	100	250
4.2	2300	2304A4H	1725	7.25	80	210
4.5	2650	2604A4H	1725	8.5	100	250
4.6	1525	1504A4H	1725	5.25	60	160
4.6	1975	2004A4H	1725	7.25	80	210
5.4	2075	2005A4H	1725	7.88	90	230
5.5	1475	1505A4H	1725	6.25	70	185
6.0	2000	2006A4H	1725	8.5	100	250
6.1	1475	1506A4H	1725	7.25	80	210
6.2	1050	1006A4H	1725	5.25	60	160
7.3	1475	1507A4H	1725	7.88	90	230
7.4	975	1007A4H	1725	5.25	60	160
8.0	1150	1208A4H	1725	7.25	80	210

\*Pumps rated for maximum 3450 rpm when motor maximum speed is 3000 rpm